



Part # Reference List

Part Number	Model Number	General Characteristics					Mechanical Package	Features
		Base Model	Operating Mode	Output Voltage	Output Current	Output Power		
20-5336	M48-U30-1670-XP	M48-U	CC	16-30V	1670mA	50-Watts	Butter Stick	AC Dimm®
20-5335	M48-U36-1390-XP	M48-U	CC	20-36V	1390mA	50-Watts	Butter Stick	AC Dimm®
20-5330	M48-U54-1050-XP	M48-U	CC	34-48V	1050mA	50-Watts	Butter Stick	AC Dimm®

Model Number Structure:

**M 48 - U 36 - 1390 - XP**

**1. 2. - 3. 4. - 5. - 6.**

- 1. Product Family:** M = Multi-Purpose Family
- 2. Output Power:** 48 = 50-Watts Max
- 3. Input Voltage:** U = 100-277VAC
- 4. Output Voltage:** 24, 30, 36, 42 & 54VDC
- 5. Output Current:** 1390 = 1390mA
- 6. Mechanical Package:** XP = Plastic, V0 Flamability Rating

Important Notes:

- A This list intended as a Part Number Reference List as such is for reference use only. New part numbers are added on a continuous basis.
- B In the event the model # or characteristics you are looking are not found on this part# list please contact your Magtech Sales Application
- C **Output Power:** Is the maximum driver Output Power Rating as defined per our UL certification.
- D **Mechanical Package:** Please refer to the Case Drawings located in the Product Documentation section of the Technical Library.
- E **Standard Features:** AC Dimm® U versions come standard with AC Trailing Edge Dimming (for ELV Dimming Controls)

**Magtech, "The Power to Drive Green Innovations"**