

Project Name:	
Type:	

WH-L03E

3 Watss Max | 100 - 304VAC

PRODUCT FEATURE

- Compact size that maximize design flexibility.
- 1.57" x 1.57" x 0.87" (LxWxH)
- Full range AC input, 100-304VAC
- Hook-up wire for easy installation
- High efficiency reduce total power consumption
- Tight regulated constant current output to maximize the LED performance
- Pre-adjusted C/C outputs

ENVIRONMENTAL

OPERATING TEMPERATURE	:	-20 to +60°C
STORAGE TEMPERATURE	:	-20 to +80°C
HUMIDITY (NON-CONDENSING)	:	5% to 95%
COOLING	:	Convection
VIBRATION FREQUENCY	:	5 to 50Hz
MTBF	:	>100,00 Hours at full load and 25°C ambient conditions (TELC3 – Telcordia SR-332, Issue 3)



WARRANTY

- See [Limited Warranty Policy](#) for more additional information.

SPECIFICATION PARAMETER	L03E-350	L03E-700	L03E-1050 ^{Note1}	L03E-12 / -24
Input Voltage (VAC)	100 ~ 304VAC			
Input Frequency (Hz)	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Output Voltage (VDC)	4 ~ 12VDC	4.5VDC	4.5VDC	12 / 24VDC
Output Current (constant)	350mA max.	700mA max.	1050mA max.	N/A
Output Power (W)	1 ~ 3 W	3 W	3 W	3 W
Short Circuit Protection	Yes			
Overload Protection	Yes			
Over-voltage Protection	Yes			
Thermal Protection	Yes			
Ambient Temperature	-20 ~ 60 Deg. C			
Storage Temperature	-20 ~ 80 Deg. C			
Max. Temperature at Tc	70 Deg. C			
Safety Approval	UL and CE certified			
Dimension	1.57"x1.57"x0.87"(LxWxH)			
Weight	55 g			
Note 1: Model(s) without UL/CE approval.				